

# DANCEFLOR

## Heterogeneous compact floor vinyl

### High performance premium Dancefloor range

Flooring for very heavy duty areas such as dance studios and theatres.

#### Features & benefits

• 0.65mm wear layer	• Excellent scratch and stain resistance
• 3.45mm thick	• Improved dancer safety
• Non woven fibreglass reinforcement layer	• Long term stability of installation • No distortion under heavy loads
• Emissions below quantifiable levels	• Optimal indoor air quality
• Matt/ satin finish	• Reduced reflected glare



### Colours

Contact Tarkett for list of stocked colours, non-stocked colours can be supplied with longer lead times

Black, Grey.



Product Characteristics	Standard	Dancefloor
Product construction	EN 649	Heterogeneous compact vinyl flooring
Classification	ISO 10874 (EN 685)	Commercial : 34
Total thickness	ISO 24346 (EN 428)	3.45mm
Wear layer thickness	ISO 24340 (EN 429)	0.65mm
Total weight	ISO 23997 (EN 430)	3295g/m <sup>2</sup>
Form of delivery	EN 426	Approx. 23lm x 2m
Warranty		10 years
Underfloor heating	EN ISO 10456	Suitable

Performance Characteristics	Standard	Dancefloor
Reaction to fire	ISO AS 9239-1	Critical radiant flux 8.6 kW/m <sup>2</sup> Smoke 186%. min
Slip Resistance	AS 4586	P3
Static electrical discharge	EN 1815	< 2 kV on concrete
Total VOC emissions	AgBB/DIBt	≤ 10 µg/m <sup>3</sup> (after 28 days)
Thermal resistance	EN 10456	Approx. 0.04m <sup>2</sup> K/W
Chemical resistance	ISO 26987 (EN 423)	High resistance
Hygiene	-	Does not contribute to infection spreading
Dimensional stability	ISO 23999 (EN 434)	≤ 0.10%
Abrasion volume loss	EN 660: Part 2	Group T: ≤ 2.0mm <sup>3</sup>
Residual indentation	ISO 24343-1 (EN 433)	≤ 0.20mm
Castor chair test	ISO 4918 (EN 425)	No damage
Curl resistance to heat	ISO 23999 (EN 434)	≤ 8mm
Light fastness	EN ISO 105-B02	≥ level 6

## Recommended specification clause for your project

Tarkett Dancefloor product number 3685\_ \_ \_ ,

- 3.45mm gauge with 0.65mm wear layer, 2m wide glass fibre reinforced heterogeneous vinyl floor covering
- TVOC below 10µg/m<sup>3</sup>
- Residual indentation ≤ 0.20mm (ISO 24343-1)
- Use area classification of 34 to EN 685 (ISO 10874)
- Manufactured in a plant with certification to ISO 9001 and ISO14001
- 10 year commercial manufacturer's product warranty
- Must be installed as per manufacturer's instructions and as per AS 1884 with matching weldrod on seams/ joints



The information in this data sheet is correct at date of publication however, due to Tarkett's commitment for ongoing product improvement, we reserve the right to change this information without notice. Please note that Tarkett's instructions regarding installation, cleaning and maintenance must be observed. Please contact Tarkett for further information on these instructions.



**For more information contact your Tarkett Sales Representative or call 1300 851 484.**

**[www.tarkett.com.au](http://www.tarkett.com.au)**



THE ULTIMATE  
FLOORING EXPERIENCE